



FLOOR MAINTENANCE – QUARTZ BASED

DURING THE INSTALLATION

- During the installation phase endeavor to leave the floor as clean as possible to avoid using abrasive products or aggressive detergents.
- Protect the floor and avoid the presence of abrasive and/or staining materials (for example: dust and residues from operations carried out after laying) as far as possible.
- Do not use abrasive pads in order to avoid damage to the fair face of the material.
- Always carry out a preliminary trial of any maintenance product on a mock-up area to verify the aesthetic effect.

DEEP CLEANING POST INSTALLATION PRE HANDOVER

- Proper washing after installation is of fundamental importance to all operations carried out afterwards and to assure correct maintenance.
- It should be remembered that machine cleaning must always be completed by hand in tight corners, along walls and any spaces that the brushing machine cannot easily reach.
- The use of alkaline detergent is allowed exceptionally in certain cases such as this (daily use will damage the floor tile)

DAILY CLEAN

- Always use a neutral detergent;
- Do not rub the surfaces using abrasive tools, such as metallic sponges or hard brushes, which could scratch the floor or leave indelible marks;
- Do not use products containing wax or shining agents;

SPECIAL TREATMENT

Special treatments such as protections, enhancer, etc. can be applied to Quarella surfaces. Before commencing these types of operations it is always better to contact the manufacturers and execute a trial area in order to evaluate the effect on the product.